



AM BRANDMASTIK

Intumeserende brandmastik

til lukning af huller i og omkring rør/kabler/kabelkanaler/ventilationsrør m.v.
i brandklassificerede dæk og vægge, samt lineær fugning.

Produkt nummer: 58

Introduction:

Halon-free, intumescent high pressure mastic with good adhesion to all materials. Available in standard colours Black, Brown, Grey, and White (other colours available). An aqueous acrylic polymer emulsion, plasticisers, inorganic extenders, reinforcing fillers, surfactants and fungicide.

Supplied in 310 ml tubes.

This product comprises of the following materials and therefore is supported by Health & Safety Data Sheets:

- Appendix 26 (AM Mastic)

*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.



HEALTH & SAFETY INFORMATION SHEET
APPENDIX 26
AM ACRYLIC ACOUSTIC INTUMESCENT MASTIC

Issue 5, February 2020

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT NAME: AM Acrylic Acoustic Intumescent Mastic.
USE: A water-borne acrylic sealant with fire and smoke resisting capability for internal gap sealing.

MANUFACTURER/SUPPLIER: Intumescent Systems Ltd
ADDRESS: Lyngvejen 7, 6900 Skjern, Denmark
TELEPHONE / EMAIL: 004532109999 / Info@envirograf.dk
EMERGENCY TELEPHONE NUMBER: 004532109999 (Monday to Friday 8.30 – 17.30)

2. HAZARDS IDENTIFICATION

Regulation EC 1272/2008

This product is not classified as hazardous according to regulation (EC) 1272/2008 (CLP)

Label Elements

Regulation EC 1272/2008

Signal word: None

Hazard statement: None

Other Hazards: None

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS No.	EC No.	REACH registration No.	Classification According to Reg. (EC) 1278/2008 (CLP)	%W W
Dipropylene Glycol Dibenzoate	27138-31-4	248-258-5	01-2119529241-49-0002	H412	<1.5 %
Proprietary blend of esters	Proprietary				4-7%

SAFETY DATA SHEET



Envirograf[®]
Produkter til brandsikring

SDS58-09-2022

4. FIRST AID MEASURES

GENERAL: In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. No emergency care anticipated.

Skin Contact: Wash skin thoroughly with soap and water or a recognised skin cleaner. **DO NOT USE SOLVENT OR THINNERS.**

EYE CONTACT: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes holding eyelids apart, and seek medical advice.

INGESTION: If accidentally swallowed wash mouth with water and give water to drink. **DO NOT** induce vomiting.

MOST IMPORTANT SYMPTOMS AND EFFECTS:

Skin Contact: No symptoms anticipated.

Eye contact: There may be irritation and redness.

Ingestion: No symptoms anticipated. If there is any persistence of discomfort seek medical assistance.

Inhalation: No symptoms.

5. FIRE FIGHTING MEASURES

The liquid product is 'non-flammable'

Extinguishing media: Recommended: alcohol resistant foam, CO₂, powder, water spray/mist.

Special hazards: As the products contain combustible organic components, the fire will produce hazardous products of combustion (see section 10) exposure to decomposition products may be a hazard to health.

Advice for firefighters: Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run off from firefighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions and protective equipment: Refer to protective measures listed in sections 7 and 8.

Environmental precautions: Do not allow to enter drains or water courses. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes, the relevant Environment Agency.

Method for containment and clean up: Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth, and place in a suitable container for disposal in accordance with the waste regulations (see section 13).



7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8.

The Manual Handling Operations Regulations: may apply to the handling of containers / packages of this product. In order to calculate the weight of any pack size, multiply the volume in litres by the specific gravity value given in section 9. This will give the net weight of the product in kilograms.

Precautions for safe storage: Keep containers closed when not in use. Never use high pressure to empty. The container is not a pressure vessel. Ensure good housekeeping and regular safe removal of waste materials. Observe label precautions - Store between 5°C and 25°C in a dry well-ventilated place away from sources of heat. Protect from frost. Keep out of reach of children. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

Engineering Measures: Provide adequate ventilation during application and drying. Where practicable this should be achieved by the use of local exhaust ventilation. If this is not sufficient to maintain concentration of solvent vapours below the relevant Occupational Exposure Limit, suitable respiratory protection must be worn (see 'Occupational Exposure Controls' below).

EXPOSURE LIMITS:

Substance	Occupational Exposure Limits	Notations
	8 hr LTEL (1) 15 min STEL(2)	
	ppm mgm ⁻³ ppm mgm ⁻³	
	«OEL68hour»	«OEL615min»

«OEL6notes»

- (1) Long-term exposure limit - 8 hour time weighted average. (SK) Risk of absorption through unbroken skin
- (2) Short-term exposure limit - 15 mins time weighted average. (Sen) Capable of causing sensitisation by inhalation
- (S) Occupational Exposure Standard (OES)
- (M) Maximum Exposure Limit (MEL)
- (R) Recommended by suppliers
- (A) Allocated limits by analogy with similar materials

OCCUPATIONAL EXPOSURE CONTROLS: All Personal Protective Equipment (ppe), including Respiratory Protective Equipment (rpe), used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

RESPIRATORY PROTECTION: If exposure to hazardous substances identified in section 8 cannot be controlled by the provision of natural ventilation e.g. work in enclosed areas, exposure should be controlled, where reasonably practicable, by the use of mechanical exhaust ventilation; when this is not reasonably practicable, suitable respiratory protective equipment must be worn.

SAFETY DATA SHEET



Envirograf[®]
Produkter til brandsikring

SDS58-09-2022

HAND PROTECTION: When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

EYE PROTECTION: Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION: Cotton or cotton/synthetic overalls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a recognised skin cleaner. ALWAYS WASH YOUR HANDS BEFORE EATING, SMOKING OR USING THE TOILET.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous paste		
Flashpoint:	>100°C		
Viscosity:	Not applicable		
Specific gravity:	«specgrav»		
Solubility in water:	Miscible when wet.		
pH:	7.7 – 8.5		
VOC:	3 g/ltr	LEED(2009) VOC	3.5 g/ltr

10. STABILITY AND REACTIVITY

Reactivity – No data available

Chemical stability – Stable under normal temperature and storage conditions

Possibility of hazardous reactions – None known

Conditions to avoid – None known

Incompatible materials – None known

Hazardous decomposition products – Oxides of carbon released under high temperature (>300°C)

11. TOXICOLOGICAL INFORMATION

Information on Toxicological effects:

There is no evidence of toxicological effects of the product.

Ingestion: May cause discomfort if swallowed. May cause stomach pain

Skin contact: May be irritating to skin

Eye contact: Risk of irritation to eyes

Sensitisation: Not sensitising

STOT: Not classified

SAFETY DATA SHEET



Envirograf[®]
Produkter til brandsikring

SDS58-09-2022

12. ECOLOGICAL INFORMATION

Ecotoxicity – Not regarded as dangerous for the environment. Not considered toxic to fish

Persistence and degradability – The product is not biodegradable

Bio accumulative potential – This product is not bio accumulating

Mobility in soil – Not mobile

Results of PBT and vPvB assessment – Not classified as PBT/vPvB

Other adverse effects – None known

13. DISPOSAL CONSIDERATION

Do not allow to enter drains or water courses. Wastes, including emptied containers, are controlled waste and should be disposed of in accordance with regulations made under the 'Control of Pollution Act' and the 'Environmental Protection Act'. Using information provided in this data sheet, advice should be obtained from the relevant Environment Agency whether the Special Waste Regulations apply.

14. TRANSPORT INFORMATION

Transport within the users premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Onwards transport subsequent to purchase: Transport to be in accordance with ADR for road, IMDG for sea and ICAO/IATA for air.

Proper shipping name: The product is not classified as dangerous for carriage.

UN number

Hazard class:

Packing group:

Sub-hazard class:

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.

Control of Substance Hazardous to Health Regulations 2002.

Environment Act 1995.

Management of Health and Safety at Work Regulations 1999.

Personal Protective Equipment at Work Regulations 2002.

Special Waste Regulations 1996 as amended.

SAFETY DATA SHEET



Envirograf[®]
Produkter til brandsikring

SDS58-09-2022

HEALTH AND SAFETY EXECUTIVE GUIDANCE NOTES

HS(G)37	An Introduction to Local Exhaust Ventilation.
EH40	Occupational Exposure Limits.
EH44	Dust: General Principles of Protection.
HS(G)53	The Selection, Use & Maintenance of Respiratory Protective Equipment.
HS(G)71	Storage of Packaged Dangerous Substances.
HS(G)1	COSHH Essentials: easy steps to control chemicals.
L23	Manual Handling Guidance Regulations.

BRITISH STANDARDS PUBLICATIONS

EN420:	General Requirements for Gloves.
EN166:	Personal Eye Protection: Specifications.
BS2092:	Eye Protection for Industrial and Non-Industrial Users.
BS4275:	Recommendations for the Selection, Use and Maintenance of Respiratory Protective Equipment.

Chemical safety assessment

16. OTHER INFORMATION

Symbols and text of the H phrases in section 2 and 3:

H412 Harmful to aquatic life with long lasting effects

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of Regulation 1272/2008 (CLP). The product should not be used for purposes other than those shown without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current EU legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.